

INTEGRITY EDGE

Quality Assurance Programme

CABINETMAKER:

SITE ADDRESS:

OHS

- New contractors to complete TAC before commencement of work (www.integritynewhomes.com.au/tradecontractorlogin username: subcontractor; password: integrity)
 - Provide project manager with SWMS (where required) and general induction numbers.
 - Ensure that you carry an Australian Standard Compliant, First Aid Kit in your vehicle at all times when on an Integrity site – this kit should be construction site & employee number appropriate.
-

PRODUCT

- Vanities and Kitchens to have drawers located against walls. Hinged doors are to be positioned away from adjacent walls due to handles hitting on the wall and preventing full opening.
- Hettich sensys soft-close door hinges.
- Standard drawer runners to be Hettich innotech with soft-close. Any additional drawers requested by the Owner during consultation must also be Hettich innotech with soft-close as a minimum.
- 16mm backs to all cabinets.
- All base and wall cabinets to have adjustable shelves, except where noted on plans as fixed.
- All board components, including laminate benchtop substrate to be minimum E1 rated.

- All melamine doors to be edged with 1mm ABS, or 2mm ABS where 1mm is not available.
- All whiteboard components edged with 1mm ABS.
- If requested, upgrades available for Vinyl, 2 pac, Timber and Timber Veneer doors.
- Laminex 'Silk' and 'Lamiwood' finish available as standard.
- Standard laminate benchtop profile to have 8mm radius on 32mm substrate. Standard option to also include 4mm radius on 38mm substrate, where the laminate is suitable i.e 'Squareform'.
- Where aluminium doors are noted on plans, the standard profile is 35mm flat, with a choice of frosted or clear inserts. A number of sizes are available.
- Cabinet made shelves to builder's pantry (if specifically marked as Cabinet Maker made) is to be 25mm thick whiteboard with 2mm ABS edging, cleated to walls with 16mm x 50mm rails.
- Minimum 7 years warranty.

INSTALLATION

- Only client signed off kitchen design drawings are to be used for the manufacture and installation of cabinetry. Preliminary or quotation only drawings are for pricing only and not to be used under any circumstances for construction.
- All cabinets installed level and plumb.
- Glue residue from stickers and edge banding removed.
- Protective film/plastic removed from doors.
- Cut-outs to laminate benchtops to be sealed with an appropriate sealer e.g Clear Silicone applied to exposed particle board from sink cut-outs.
- Silicone seal and glue applied to benchtop joins prior to toggle bolt clamping.
- Silicone seal to laminate tops where they butt up against walls.

Date:

- Bump-on's applied to all opening fronts (except integrated appliances).
- Screw heads capped.
- Maximum 3mm gap tolerance between cabinet fronts.
- Kicker to be reinforced when distance between adjustable legs exceeds 900mm.
- Access point for DW and WM set up. Move rear leg and 'box' an entry point.
- Cabinetry vermin proofed, including DW and WM access.
- Skirting boards and architraves that have been removed to facilitate cabinetry installation must be re-cut and fixed back to wall.
- Standard sized cutlery trays to be fixed to position in oversized drawers.
- Handles, unless location is specifically nominated, are to be placed 50mm in from door edges
- All end panels finished against walls with paintable gap sealer where required.
- All rubbish removed from site or placed in the site bin provided.
- Complete and sign Integrity Edge and submit with invoice at end of job.

Installers Signature: _____ Date: _____

Print Name: _____ Invoice No: _____